## **HellermannTyton**



Article Number: 170-03012

Braided Sleeving, Expandable, Fray Resistant, .5" Dia,

PET, Black, 100 ft/reel

Base Data Local Order Number 170-03012 BSPSC120 Type Color Black (BK) Features and Benefits · Cuts with scissors without fraying ends enables field installations without need for hot knife. · Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus. • Expands to 150% of easy installation and reduced assembly time requirements. Quantity Per reel Product Description A versatile and economical general purpose braided sleeving that resists fraying when cut with ordinary scissors. Short Description Braided Sleeving, Expandable, Fray Resistant, .5" Dia, PET, Black, 100 ft/reel Product Dimensions Length L (Imperial) 100.0ft Length L (Metric) 30.48m Reel Length (imperial) 100.0ft Bundle Diameter Min. (Imperial) 0.25" Bundle Diameter Min. (Metric) 6.4mm 0.75" Bundle Diameter Max. (Imperial) Bundle Diameter Max. (Metric) 19.1mm Nominal Diameter (Imperial) 1/2" Nominal Diameter (Metric) 12.7mm Material and Specifications Material Polyester (PET) Material Shortcut PET Flammability UL 94 V0

## 170-03012

## **HellermannTyton**

Material and Specifications	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100ft
	Package Quantity (Metric)	30.48m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	0.82lbs
	Weight (Metric)	0.37kg