

170-03054



Article Number: 170-03054

Description: Braided Sleeving, Aluminum Laminated Fiberglass, .5" Dia, AL/GF, Silver, 250 ft/bulk reel

Base Data	Local Order Number	170-03054
	Type	BSHTTST12SRB
	Color	Silver (SR)
	Features and Benefits	<ul style="list-style-type: none"> <li>• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.</li> <li>• Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.</li> <li>• Cuts with ordinary scissors for fast, easy application.</li> </ul>
	Quantity Per	reel
	Product Description	A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.
	Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, .5" Dia, AL/GF, Silver, 250 ft/bulk reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		76.2m
Reel Length (imperial)		250.0ft
Bundle Diameter Max. (Imperial)		0.437"
Bundle Diameter Max. (Metric)		11.1mm
Diameter D (imperial)		0.5"
Diameter D (metric)		12.7mm
Nominal Diameter (Imperial)		1/2"
Nominal Diameter (Metric)		12.7mm
Material and Specifications	Material	Aluminum (AL)
	Material Shortcut	GF

170-03054



Material and Specifications	Flammability	non flammable
	Operating Temperature	-76°F to +491°F (-60°C to +255°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	250ft
	Package Quantity (Metric)	76.2m
	Customs Number(Schedule B)	7019901000
	Weight (imperial)	6.375lbs
	Weight (Metric)	2.90kg