

Article Number: 181-00483



Description: Solid Cable and Wiring Duct, 1.5" x 1.5", Adhesive, PVC,

Gray, 120 ft/carton

| Base Data             |                                  |  |
|-----------------------|----------------------------------|--|
|                       |                                  |  |
|                       | Local Order Number               | 181-00483  |
|                       | Туре                             | SDA1.5X1.5   |
|                       | Color                            | Gray (GY)  |
|                       | Features and Benefits            | <ul> <li>A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.</li> <li>Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.</li> <li>Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)</li> </ul> |
|                       | Quantity Per                     | carton   |
|                       | Product Description              | HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.   |
|                       | Technical Description            | Adhesive   |
|                       | Short Description                | Solid Cable and Wiring Duct, 1.5" x 1.5", Adhesive, PVC, Gray, 120 ft/carton   |
| Product<br>Dimensions |                                  |  |
|                       | Length L (Imperial)              | 6.0ft  |
|                       | Length L (Metric)                | 1.83m  |
|                       | Width W (Imperial)               | 1.5"   |
|                       | Width W (Metric)                 | 38.1mm   |
|                       | Width W2 (Imperial)              | 1.5"   |
|                       | Width W2 (Metric)                | 38.1mm   |
|                       | Height H (Imperial)              | 1.57"  |
|                       | Height H (Metric)                | 39.9mm   |
|                       | Mounting Hole Centers (Imperial) | 4.0"   |

generated on: 4/28/2017

## 181-00483



| Material and Specifications |                             |                         |
|-----------------------------|-----------------------------|-------------------------|
|                             | Material                    | Polyvinylchloride (PVC) |
|                             | Material Shortcut           | PVC                     |
|                             | Flammability                | self-extinguishing      |
|                             | Operating Temperature       | +122°F (+50°C)          |
|                             | ROHS Compliant              | Yes                     |
|                             | Certification/Specification | UL                      |
|                             | UL Recognized (US)          | Yes                     |
| Logistic and<br>Packaging   |                             |                         |
|                             | Package Quantity (Imperial) | 120ft                   |
|                             | Package Quantity (Metric)   | 36.6m                   |
|                             | Customs Number(Schedule B)  | 3925900000              |

generated on: 4/28/2017