


FLKM 14-PA-INLINE/32


Order No.: 2302777

The illustration shows the version FLKM 14-PA-INLINE/IN16



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2302777>

VARIOFACE front adapter, for 16-channel Inline modules, input IB IL 24 DI 32/HD and output IB IL 24 DO 32/HD

Commercial data	
GTIN (EAN)	 4 017918 929466
sales group	I661
Pack	1 pcs.
Customs tariff	85369010
Catalog page information	Page 227 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
08/10/2006




<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
General	
Nominal voltage U_N	60 V DC
Channels which can be connected	32
Connection type, plug connector	Flat-ribbon cable plug connector in acc. with IEC 60603-13
Number of plug connectors	4


No. of positions, plug connector	14
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Mounting position	Any
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Max. permissible current	1 A (per path)

Diagrams/Drawings

Connection diagram



Circuit diagram



Connection scheme: FLKM 14-PA-INLINE/32

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;