

# NetDirector DVI USB Server Interface Unit with Virtual Media and CAC Support (B064-IPG Series), USB and DVI

MODEL NUMBER: B055-001-UDV











#### Description

The B055-001-UDV NetDirector® DVI USB Server Interface Unit connects a server, computer or CAC reader with DVI and/or USB ports to a Tripp Lite B064-IPG Series KVM switch with v1.0.071 or later firmware installed. Using Cat5e/6 cabling, you can locate the KVM switch up to 164 feet (50 meters) from the server.

# **Highlights**

- Provides connected USB/DVI server with Virtual Media access
- Supports Common Access Card (CAC)
- Eliminates thick, heavy KVM cable kits
- Ideal for running cable through conduit and other tight spaces
- Plug-and-play—no software or power supply required

#### **System Requirements**

- Server, CPU or CAC reader with DVI and USB ports
- B064-IPG Series KVM switch with v1.0.071 or later firmware installed
- Cat5e/6 cable

# **Package Includes**

 B055-001-UDV NetDirector DVI USB Server Interface Unit

Allowing the server to access the KVM switch's Virtual Media functionality via low-cost Cat5e/6 cable eliminates the need for bulky KVM cables. This frees up precious space in your server cabinet, and allows for better ventilation and longer cable runs. Running cable through conduit and other tight spaces takes advantage of the increased flexibility when setting up your network application.

No software or external power supply is needed. The unit's compact, lightweight design is plug-and-play for immediate installation and deployment. It complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

#### **Features**

# Convenient, Cost-Effective KVM Connection

- Connects USB/DVI server to Tripp Lite B064-IPG Series KVM switch with v1.0.071 or later firmware via Cat5e/6 cable
- Allows server to access Virtual Media functionality
- Supports Common Access Card (CAC)
- Maximum distance between server and KVM switch of 164 ft. (50 m)

### **Eliminates Bulky KVM Cables**

- Frees precious space in server cabinet
- · Provides better ventilation and longer cable runs
- More flexibility for running cable through conduit and other tight spaces

## Plug-and-Play Convenience



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

- No software or external power supply required
- Ready for immediate installation and deployment

#### **TAA-Compliant**

• Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

# **Specifications**

OVERVIEW	
Accessories Type	Server Interface Unit
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies