

Article Number: 181-12012

Description: Slotted Cable and Wiring Duct, 1" x 2", Adhesive, PVC,

HellermannTyton

White, 30ft/box

Base Data		
	Local Order Number	181-12012
	Туре	SLA1X2
	Color	White (WH)
	Features and Benefits	<ul> <li>Strong fingers prevent unwanted breaking.</li> <li>Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.</li> <li>Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.</li> </ul>
	Quantity Per	box
	Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".
	Technical Description	Adhesive
	Short Description	Slotted Cable and Wiring Duct, 1" x 2", Adhesive, PVC, White, 30ft/box
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.0"
	Width W (Metric)	25.4mm
	Width W2 (Imperial)	1.0"
	Width W2 (Metric)	25.4mm
	Width W3 (Imperial)	0.4"
	Width W3 (Metric)	10.2mm
	Width W4 (imperial)	1.0"
	Width W4 (metric)	25.4mm
	Width W5 (imperial)	1.62"
	Width W5 (metric)	41.1mm

generated on: 4/28/2017

## 181-12012



Product Dimensions         Height H (Imperial)         2.07"           Height H (Metric)         52.6mm           Mounting Hole Centers (Imperial)         4.0"           Material and Specifications         Polyvinylchloride (PVC)           Material Shortcut         PVC           Flammability         self-extinguishing           Operating Temperature         +122°F (+50°C)           ROHS Compliant         Yes           Certification/Specification         UL
Height H (Metric)  Mounting Hole Centers (Imperial)  Material and Specifications  Material  Material  Polyvinylchloride (PVC)  Material Shortcut  PVC  Flammability  Operating Temperature  H122°F (+50°C)  ROHS Compliant  Yes
Material and Specifications  Material Polyvinylchloride (PVC)  Material Shortcut PVC  Flammability self-extinguishing  Operating Temperature +122°F (+50°C)  ROHS Compliant Yes
Material Polyvinylchloride (PVC)  Material Shortcut PVC  Flammability self-extinguishing  Operating Temperature +122°F (+50°C)  ROHS Compliant Yes
Material Shortcut PVC  Flammability self-extinguishing  Operating Temperature +122°F (+50°C)  ROHS Compliant Yes
Flammability self-extinguishing  Operating Temperature +122°F (+50°C)  ROHS Compliant Yes
Operating Temperature +122°F (+50°C)  ROHS Compliant Yes
ROHS Compliant Yes
Certification/Specification III
Oct uncation/opecinication
UL Recognized (US) Yes
Logistic and Packaging
Package Quantity (Imperial) 30.0ft
Package Quantity (Metric) 9.1m
Customs Number(Schedule B) 3925900000

generated on: 4/28/2017