

155-12300

Article Number: 155-12300

Description: Oval Stud Mount Cable Tie, Designed for 5.0 mm stud, 6.0 Long, PA66HS, Black, 500/pkg



Base Data	Local Order Number	155-12300
	Type	T50SOSSBS5E
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • Oval mount design pushes on easy by hand without the need for tools. • Design provides low insertion and high extraction force.
	Quantity Per	bag
	Product Description	The special oval shape provides for an approximate .20" (5.0 mm) lateral adjustment, allowing for any misalignment of the stud or incorrect positioning of the tie on the cables
	Short Description	Oval Stud Mount Cable Tie, Designed for 5.0 mm stud, 6.0 Long, PA66HS, Black, 500/pkg
Product Dimensions	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	225N
	Length L (Imperial)	6.0"
	Length L (Metric)	160.0mm
	Fixation Method	Weld Stud Fixing
	Identification Plate Position	none
	Releasable Closure	No
	Tie Closure	plastic pawl
	Variant	Outside Serrated
	Width W (Imperial)	0.19"
	Width W (Metric)	4.7mm
	Width W2 (Imperial)	0.5"
	Width W2 (Metric)	12.0mm
	Height H (Imperial)	0.06"
	Height H (Metric)	1.35mm

155-12300



Product Dimensions	Height H2 (Imperial)	0.6"
	Height H2 (Metric)	15mm
	Bundle Diameter Min. (Imperial)	0.04"
	Bundle Diameter Min. (Metric)	1.0mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Stud Length min (metric)	8.0mm
	Stud Length Max. (Metric)	14.0mm
	Thickness T (Imperial)	0.05"
	Thickness T (Metric)	1.35mm
	Stud Size (Imperial)	0.2"
	Stud Size (Metric)	5.0 mm
	Material and Specifications	
Material		Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut		PA66HS
Flammability		UL 94 HB
Operating Temperature		-40°F to +221°F (-40°C to +105°C)
REACH Compliant (Article 33)		Yes
ROHS Compliant		Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	2.85kg