



NOTE: DIMENSIONS IN MILLIMETERS, INCHES IN PARENTHESES.

MATERIAL NUMBER	OLD PART NUMBER
1201140066	BTY801P-FBC

VOLTAGE RATING	10-30 VDC
AMPERAGE RATING PER PORT	4 AMPS
PROTECTION	IP67
OPERATING TEMPERATURE	-25°C TO +90°C
UL CERTIFICATIONS	UL RECOGNIZED, FILE NO. E46237
CSA CERTIFICATIONS	CSA CERTIFIED, FILE NO. LR6837

ITEM	COMPONENT	MATERIAL	FINISH
1	CONTACT SOCKET	COPPER ALLOY	GOLD OVER NICKEL
2	O-RING	VITON	RED
3	RECEPTACLE SHELL	BRASS	NICKEL PLATED
4	HOUSING	PBT	YELLOW
5	LABEL	ABS	WHITE
6	LENS	NYLON	CLEAR

DESCRIPTION EC NO: WEU2010-0452 DRWN: BBRAUCH 2010/03/19 CHKD: FP APPR: FPACHER 2010/03/24	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
	▼ = 0 ▽ = 0	mm INCH 4 PLACES ±--- ±--- 3 PLACES ±--- ±--- 2 PLACES ±--- ±.01 1 PLACE ±0.3 ±--- ANGULAR ± --- °	MM ONLY	2:1	METRIC	
1	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	see table	DRAWN BY BBRAUCH	DATE 2010/03/19	MICRO-CHANGE MPIS TOP MOUNT 8PORT PNP -CONNECT	
REV			CHECKED BY FP	DATE 2010/03/19		
			APPROVED BY FPACHER	DATE 2010/03/23	MOLEX INCORPORATED	
			MATERIAL NO.	DOCUMENT NO.		
			SIZE A2	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		SHEET NO. 1 OF 1