



NOTES:

- 1. CAPTURED CENTER CONTACT
- 2. MATERIAL:

CENTER CONDUCTOR: BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, COND. H OUTER CONDUCTOR: STAINLESS STEEL PER ASTM A484 & A582, TYPE 303 DIELECTRIC: TEFLON PER ASTM-D-1457

3. FINISH:

CENTER CONDUCTOR: GOLD PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290 OUTER CONDUCTOR: PASSIVATE PER QQ-P-35

DESIGN CONTROL REQUIRED

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±005 ± 1°	DRAWN BY Come 3/21/95 CHECKED BY APPD BY Come 3/21/95		140	Incorporated Fourth Avenue tham, MA 02451-7599		
These drawings and specificat- lons are the property of M/A-COM incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of Item(s) without written permission.	USE ASS'Y PROCEDURE	TITLE OS-50 JACK TO 3,5mm JACK				
	N/A NO. AP	sze B	000E DENT NO. 26805	1250-22	77-02	01 ₀
		SCALE	6:1		SHEET 1 0	F 1

CUSTOMER DRAWING

AMP PART # 1046304-1 SHEET 1 OF 1 REV A