## **HellermannTyton**



Article Number: 170-03103

Description: Plenum Rated Expandable Braided Sleeving (Halar), .38"

Dia, WH, 125 ft/reel

| Base Data                      |                                 |  |
|--------------------------------|---------------------------------|--|
|                                |                                 |  |
|                                | Local Order Number              | 170-03103  |
|                                | Туре                            | BSHLR3810  |
|                                | Color                           | White (WH)   |
|                                | Features and Benefits           | <ul> <li>Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.</li> <li>Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.</li> <li>Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.</li> </ul> |
|                                | Quantity Per                    | reel   |
|                                | Product Description             | Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.   |
|                                | Short Description               | Plenum Rated Expandable Braided Sleeving (Halar), .38" Dia, WH, 125 ft/reel  |
| Product<br>Dimensions          |                                 |  |
|                                | Length L (Imperial)             | 125.0ft  |
|                                | Length L (Metric)               | 38.1m  |
|                                | Reel Length (imperial)          | 125.0ft  |
|                                | Bundle Diameter Min. (Imperial) | 0.187"   |
|                                | Bundle Diameter Min. (Metric)   | 4.8mm  |
|                                | Bundle Diameter Max. (Imperial) | 0.63"  |
|                                | Bundle Diameter Max. (Metric)   | 16.0mm   |
|                                | Nominal Diameter (Imperial)     | 3/8"   |
|                                | Nominal Diameter (Metric)       | 9.5mm  |
| Material and<br>Specifications |                                 |  |
|                                | Material                        | Polyamide 6.6 (PA66E/CTFE)   |
|                                | Material Shortcut               | PA66E/CTFE   |
|                                | Flammability                    | UL VW-1  |
|                                |                                 |  |

generated on: 4/28/2017

## 170-03103



| Material and<br>Specifications | Operating Temperature         | -103°F to +302°F (-75°C to +150°C) |
|--------------------------------|-------------------------------|------------------------------------|
|                                | ROHS Compliant                | Yes                                |
|                                | Certification/Specification   | UL2024                             |
|                                | UL Recognized (US and Canada) | Yes                                |
| Logistic and Packaging         |                               |                                    |
|                                | Package Quantity (Imperial)   | 125ft                              |
|                                | Package Quantity (Metric)     | 38.1m                              |
|                                | Customs Number(Schedule B)    | 3926909987                         |
|                                | Weight (imperial)             | 1.08lbs                            |
|                                | Weight (Metric)               | 0.49kg                             |

generated on: 4/28/2017