



## NOTES:

- 1. MATERIAL: NYLON 6/6 UL 94 V-2 (RMS-01). NYLON 6/6 UL 94 V-0 (RMS-19), AVAILABLE BY SPECIAL ORDER ONLY. TO ORDER REPLACE "-01" WITH "-19".
- 2. COLOR: NATURAL.
- 3. ALTERNATE UNITS FOR REFERENCE ONLY
- 4. PACKAGING QUANTITIES ARE REFLECTED AS THE SUFFIX "-LETTER"

EXAMPLE: FTH-3-01-M FOR 1000 PCS PER BAG.

-C = 100 PCS

-M = 1000 PCS

|          |                                   |       |          | FLAT TIE HOLDER, STYLE #3   |                  |      |                                    |              | DWG IN IN [MM]                             |          |       |
|----------|-----------------------------------|-------|----------|-----------------------------|------------------|------|------------------------------------|--------------|--|----------|-------|
| <u> </u> |                                   | Tarr  |          | CREATED USING<br>SOLIDWORKS | FILE #: F7       | ГН-3 |                                    | DWN: SK      | APP: RT                                    | FINAL    |       |
|          | SEE CO 200661 FOR CHANGES         | SK    | 05.12.11 | TOLERANCES                  | SHEET: 1         | OF 1 | SHEET SIZE: A                      | DT: 09/26/06 | CHKD: DZ                                   | PART#    | PRINT |
| Н        | SEE CO 200570 FOR CHANGES         | SK    | 08/04/10 |                             | RE: RICHCO, INC. |      |                                    |              |  | 1        | TYPE  |
| G        | SEE ECN #1224 FOR CHANGES         | SK    | 09/26/06 | .XX=±.010<br>.XXX=±.005     |                  |      | RICHCO, INC.<br>ENG@RICHCO-INC.COM |              |  | <u> </u> |       |
| -        | SEE ENGINEERING FOR REVISIONS A-F |       |          | FRAC.=±1/64                 | ,                |      |                                    |              | <b>                                   </b> | (A)      |       |
| REV.     | DESCRIPTION                       | ENGR. | DATE     | ANG.=±1°                    |                  |      |                                    | (773) 5      | 39-4060                                    |          |       |